



Item# _____

Job _____



Casters Stem-Type

Standard



5MB Wheel Brake



5M Resilient

Stainless Steel, Cart Washable



5MDBGSA



5MDGSA

Polymer Casters



5PC



5PCB

METRO™ STEM CASTERS

- **Metro Stem-Type Casters** are designed to fit Super Erecta Shelf® posts to form shelf carts and other mobile units.
- **Stainless Steel, Cart-Washable Casters** offer grease seals and zerk fittings. Can withstand high-pressure washings.
- **Polymer Casters:** Innovative polymer stem casters offer total corrosion resistance and enhanced durability. For all medium-duty applications.
- **Resilient Rubber Tread:** A molded, soft tread that provides good floor protection along with quiet operation. Non-marking.
- **Polyurethane Tread:** Long-wearing; resists abrasion. Non-marking, shock absorbing.
- **Wheel Brakes:** Foot-operated. Available on all caster models.
- **Caster Load Ratings:** From 125 lbs. to 300 lbs. (57 to 136kg).
- **Donut Bumpers:** Furnished standard on all Metro stem casters.
- **Additional Caster Types Available.**

Note: SPECIAL WHEELS — V-groove, Conductive, Steel and Phenolic — are available on request. For additional information, contact InterMetro Industries Corporation or your InterMetro representative.



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



METRO™ STEM CASTERS

DIMENSIONS: Standard Casters — Stem-Type

Cat. No.	Type	Wheel Dia.		Face		Wheel Tread	Load Rating		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	(lbs.)	(kg)
4LD	Stem/Swivel	4	102	1/2	12	Resilient	125	56	1 1/2	.6
5LD	Stem/Swivel	5	127	1/2	12	Resilient	125	56	2	.9
5M	Stem/Swivel	5	127	1 1/4	32	Resilient	200	90	2 1/2	1.1
5MB	Stem/Brake	5	127	1 1/4	32	Resilient	200	90	2 3/4	1.2
5MR	Stem/Rigid	5	127	1 1/4	32	Resilient	200	90	3 1/2	1.5
5MDA	Stem/Swivel	5	127	1 1/4	32	High Modulus Donut	250	111	2 1/2	1.1
5MDBA	Stem/Brake	5	127	1 1/4	32	High Modulus Donut	250	111	2 5/8	1.17
5MDRA	Stem/Rigid	5	127	1 1/4	32	High Modulus Donut	250	111	2 5/8	1.08
5MP	Stem/Swivel	5	127	1 1/4	32	Polyurethane	300	135	2 1/8	.94
5MPB	Stem/Brake	5	127	1 1/4	32	Polyurethane	300	135	2 1/4	1
5MPR	Stem/Rigid	5	127	1 1/4	32	Polyurethane	300	135	2	.9

- NOTE 1: Stem casters are shipped with donut bumper **at no additional charge.**
- NOTE 2: Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.
- NOTE 3: Load Height for all 5M, 5MD and 5MP casters — 6 7/32" ± 1/16" (155 ± 1.5mm).
- NOTE 4: Load Height for 4LD caster — 4 5/8" ± 1/16" (118 ± 1.5mm).
- NOTE 5: Load Height for 5LD caster — 5 5/8" ± 1/16" (143 ± 1.5mm).
- NOTE 6: Brakes are foot-operated.

DIMENSIONS: Stainless Steel Cart-Washable Casters — Stem-Type

Cat. No.	Type	Wheel Dia.		Face		Wheel Tread	Load Rating		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	(lbs.)	(kg)
5MDGSA	Swivel	5	127	1 1/4	32	High Modulus Donut	150	68	2 1/2	1.1
5MDBGSA	Brake	5	127	1 1/4	32	High Modulus Donut	150	68	2 5/8	1.17
5MDRGSA	Rigid	5	127	1 1/4	32	High Modulus Donut	150	68	2 5/8	1.08
5MPGSA	Swivel	5	127	1 1/4	32	Polyurethane	300	135	2 1/8	.94
5MPBGSA	Brake	5	127	1 1/4	32	Polyurethane	300	135	2 1/4	1
5MPRGSA	Rigid	5	127	1 1/4	32	Polyurethane	300	135	2	.9

- NOTE 1: Stem casters are shipped with donut bumper **at no extra charge.**
- NOTE 2: Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.
- NOTE 3: Load Height for all 5MD and 5MP casters — 6 7/32" ± 1/16" (155 ± 1.5mm).
- NOTE 4: All casters are grease sealed with zerk fittings in swivel and axle.
- NOTE 5: Brakes are foot-operated.
- NOTE 6: "D" in model number designates donut wheel made of high-modulus rubber.

DIMENSIONS: Polymer Casters — Stem-Type

Cat. No.	Type	Wheel Dia.		Face		Wheel Tread	Load Rating		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	(lbs.)	(kg)
5PC	Swivel	5	127	1 1/4	32	Polyurethane	300	135	2	.9
5PCB	Brake	5	127	1 1/4	32	Polyurethane	300	135	2	.9
5PCR	Rigid	5	127	1 1/4	32	Polyurethane	300	135	2	.9

- NOTE 1: Optional thread guards (blue) may be ordered by adding "-TG" to the desired model number (eg. 5PC-TG, 5PCB-TG, 5PCR-TG)
- NOTE 2: Stem casters are shipped with donut bumpers **at no extra charge.**
- NOTE 3: Rigid casters are held in place by a connecting channel. When ordering, shelf depth **must be** provided.

Manufactured by:
InterMetro Industries Corp.
 North Washington Street
 Wilkes-Barre, PA 18705

Phone 717-825-2741
 FAX 717-825-2852
 For Product Information, call 1-800-433-2232
 For Customer Service, call 1-800-992-1776



InterMetro Industries Corporation
 North Washington Street
 Wilkes-Barre, PA 18705
 www.metro.com

